

SITOP PSU200M/1-2AC/24VDC/5A  
 SITOP PSU200M 5 A Stabilized power supply input: 120/230-500 V  
 AC output: 24 V DC/5 A



Input	
Input	1-phase and 2-phase AC
<ul style="list-style-type: none"> <li>Note</li> </ul>	Set by means of selector switch on the device; starting from $V_{in} > 90/180$ V
supply voltage	
<ul style="list-style-type: none"> <li>1 at AC</li> <li>2 at AC</li> </ul>	120 ... 230 V 230 ... 500 V
input voltage	
<ul style="list-style-type: none"> <li>1 at AC</li> <li>2 at AC</li> </ul>	85 ... 264 V 176 ... 550 V
Wide-range input	Yes
Overvoltage resistance	1300 V <sub>peak</sub> , 1.3 ms
Mains buffering	at $V_{in} = 120/230$ V, typ. 150 ms at $V_{in} = 400$ V
Mains buffering at lout rated, min.	25 ms; at $V_{in} = 120/230$ V, typ. 150 ms at $V_{in} = 400$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
<ul style="list-style-type: none"> <li>at rated input voltage 120 V</li> </ul>	2.2 A

<ul style="list-style-type: none"> <li>• at rated input voltage 230 V</li> <li>• at rated input voltage 500 V</li> </ul>	1.2 A 0.61 A
Switch-on current limiting (+25 °C), max.	35 A
I <sup>2</sup> t, max.	1.7 A <sup>2</sup> ·s
Built-in incoming fuse	T 3.15 A (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker at 1-phase operation: from 6 A (10 A) characteristic C (B); required at 2-phase operation: circuit breaker 2-pole connected or circuit breaker 3RV2011-1EA10 (setting 3.8 A) or 3RV2711-1ED10 (UL 489) at 230 V; 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489) at 400/500 V

## Output

Output	Controlled, isolated DC voltage
Rated voltage V <sub>out</sub> DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	200 mV
Adjustment range	24 ... 28.8 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
Signaling	via signaling module (6EP1961-3BA10)
On/off behavior	Overshoot of V <sub>out</sub> approx. 3 %
Startup delay, max.	1 s
Voltage rise, typ.	50 ms
Rated current value I <sub>out</sub> rated	5 A
Current range	0 ... 5 A
supplied active power typical	120 W
short-term overload current	
<ul style="list-style-type: none"> <li>• at short-circuit during operation typical</li> </ul>	15 A
duration of overloading capability for excess current	
<ul style="list-style-type: none"> <li>• at short-circuit during operation</li> </ul>	25 ms
constant overload current	
<ul style="list-style-type: none"> <li>• on short-circuiting during the start-up typical</li> </ul>	5.5 A
Parallel switching for enhanced performance	Yes; switchable characteristic
Numbers of parallel switchable units for enhanced performance	2

## Efficiency

Efficiency at V <sub>out</sub> rated, I <sub>out</sub> rated, approx.	87 %
Power loss at V <sub>out</sub> rated, I <sub>out</sub> rated, approx.	18 W

## Closed-loop control

Dynamic mains compensation ( $V_{in}$ rated $\pm 15\%$ ), max.	0.1 %
Dynamic load smoothing ( $I_{out}$ : 50/100/50 %), $U_{out} \pm$ typ.	3 %
Load step setting time 50 to 100%, typ.	2 ms
Load step setting time 100 to 50%, typ.	2 ms
setting time maximum	5 ms

### Protection and monitoring

Output overvoltage protection	< 35 V
Current limitation, typ.	5.5 A
property of the output short-circuit proof	Yes
Short-circuit protection	Alternatively, constant current characteristic approx. 5.5 A or latching shutdown
enduring short circuit current RMS value <ul style="list-style-type: none"> <li>• typical</li> </ul>	5.5 A
Overload/short-circuit indicator	LED yellow for "overload", LED red for "latching shutdown"

### Safety

Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage $U_{out}$ acc. to EN 60950-1 and EN 50178
Protection class	Class I
leakage current <ul style="list-style-type: none"> <li>• maximum</li> <li>• typical</li> </ul>	3.5 mA 0.25 mA
Degree of protection (EN 60529)	IP20

### Approvals

CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
Explosion protection	-
certificate of suitability NEC Class 2	No
FM approval	-
CB approval	No
Marine approval	ABS, GL

### EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

### environmental conditions

ambient temperature <ul style="list-style-type: none"> <li>• during operation <ul style="list-style-type: none"> <li>— Note</li> </ul> </li> <li>• during transport</li> </ul>	-25 ... +70 °C with natural convection -40 ... +85 °C
--	---

• during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, 5 ... 95% no condensation
<b>Mechanics</b>	
Connection technology	screw-type terminals
Connections	
• Supply input	L, N, PE: 1 screw terminal each for 0.2 ... 2.5 mm <sup>2</sup> single-core/finely stranded
• Output	+, -: 2 screw terminals each for 0.2 ... 2.5 mm <sup>2</sup>
• Auxiliary	-
width of the enclosure	70 mm
height of the enclosure	125 mm
depth of the enclosure	125 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
Weight, approx.	1.2 kg
product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
electrical accessories	Buffer module, signaling module
MTBF at 40 °C	885 740 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)